

DECLARATION OF PERFORMANCE No. 5/2013

Product – identification code for product type	Hot rolled products of non-alloy structural steels quality grade S235JR(J0,J2), S275JR(J0,J2), S355JR(J0,J2)
Type designation	- wide steel 150 till 600 mm, thickness 5 till 70 mm
Intended use	The production of metallic elements, components, assemblies and structures
Manufacturer	TŘINECKÉ ŽELEZÁRNY, a.s. Průmyslová 1000, Staré Město 739 61 Třinec, Czech Republic
Production mill	department VHb – Universal Mill Bohumín areál ŽDB a.s. 735 93 Bohumín, Czech Republic
Authorized representative	Was not appointed
The system of assessment and verification of characteristics constancy	2+
Notified body	TZUS Praha s.p. Prosecká 811/76a, Praha 9, č. NB 1020 Certificate no. 1020-CPD-070030003

Characteristics stated in Declaration: (acc. to table ZA.1 EN 10025-1)

Basic characteristics	Requirements on characteristic	Harmonized tech. specification
Tolerances on dimensions and shape - wide steel	EN 10058, DIN 59200	7.7.1 EN 10025-1
Elongation	EN 10025-2, tab.7	7.3.1 EN 10025-1
Tensile strength	EN 10025-2, tab.7	7.3.1 EN 10025-1
Yield strength	EN 10025-2, tab.7	7.3.1 EN 10025-1
Impact strength	EN 10025-2, tab.9	7.3.1 + 7.3.2 EN 10025-1
Weldability (chem. composition)	EN 10025-2, tab.2, tab.4, tab.6	7.2 + 7.4.1 EN 10025-1
Life durability (chem. composition)	EN 10025-2, tab.2, tab.4	7.2 + 7.4.3 EN 10025-1

Product characteristics are in conformity with the characteristic stated in the table.

This Declaration of Performance is issued under the sole responsibility of the manufacturer.

Enclosure No. 1 – Information on CE marking – is part of this Declaration of Performance.

In Třinec 2013-07-01




TŘINECKÉ ŽELEZÁRNY, a.s.
Průmyslová 1000, Staré Město
739 61 Třinec 16

Ing. Radim Raszka

Head of Quality Assurance

Enclosure no.1 – Information on CE marking

 NB 1020	
TŘINECKÉ ŽELEZÁRNY, a.s. Průmyslová 1000, Staré Město, 739 61 Třinec IČ: 18050646 06 1020-CPD-070030003	
EN 10025-1 Hot rolled products of non-alloy structural steels quality grade S235JR(J0,J2), S275JR(J0,J2), S355JR(J0,J2) – wide steel Intended use: The production of metallic elements, components, assemblies and structures	
DECLARATION OF PERFORMANCE No. 5/2013	
Tolerances on dimensions and shape	EN 10058, DIN 59200
Elongation	EN 10025-2, tab.7
Tensile strength	EN 10025-2, tab.7
Yield strength	EN 10025-2, tab.7
Impact strength	EN 10025-2, tab.9
Weldability (chem. composition)	EN 10025-2, tab.2, tab.4, tab.6
Life durability	Not applicable
Monitored substances	Not applicable